

THOMSON
DELPHION

RESEARCH

PRODUCTS

INSIDE DELPHION

My Account | Products

Search: Quick/Number Boolean Advanced

The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#)Tools: Add to Work File: [Create new Wor](#)View: [INPADOC](#) | Jump to: [Top](#)  Go to: [Derwent...](#) [Ema](#)Title: **JP11260372A2: MANUFACTURE OF NONAQUEOUS SECONDARY B**Country: **JP Japan**Kind: **A**Inventor: **FURUKAWA SANEHIRO;
FUJIMOTO MASAHISA;
YOSHINAGA NORIYUKI;
UENO KOJI;**Assignee: **SANYO ELECTRIC CO LTD**
[News, Profiles, Stocks and More about this company](#)Published / Filed: **1999-09-24 / 1999-01-14**Application Number: **JP1999000008215**IPC Code: **H01M 4/66; H01M 2/02; H01M 4/02; H01M 10/40;**Priority Number: **1999-01-14 JP1999019998215**

Abstract:

.... PROBLEM TO BE SOLVED: To improve the cycle characteristic and load characteristic, while preventing the elution of a collector by constructing a positive electrode collector and/or a positive electrode armor of aluminum with aluminum oxide coating on the surface and having lithium intercalate into a negative electrode material by injecting an electrolyte.

.... SOLUTION: A positive electrode collector is constructed of an aluminum foil with the surface covered with aluminum oxide. By mixing petroleum coke with N-methylpyrrolidone solution, in which polyvinylidene fluoride is dissolved, a mixed solution is prepared. Next, by applying this mix solution to a negative electrode collector made of copper foil and then bringing the negative collector into contact with lithium foil, a negative electrode 2 is formed. Lithium on the negative electrode 2 is intercalated into the petroleum coke serving as a negative electrode material after injecting the electrolyte. Then, a separator 3 is arranged between the positive electrode 1 and the negative electrode 2, and these are wound up into a spiral shape and form a group 4 of electrodes.

.... COPYRIGHT: (C)1999,JPO

Family: **None**Other Abstract Info: **DERABS C1999-596408 DERABS C1999-596408**



[Nominate](#)

[this for the Gallery...](#)

© 1997-2003 Thomson Delphion

[Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact](#)


THOMSON
*
DELPHION**RESEARCH****PRODUCTS****INSIDE DELPHION**

Log On | My Account | Products

My Account | Products

Search: Quick/Number Boolean Advanced

The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#)Tools: Add to Work File: [Create new Wor](#)View: [INPADOC](#) | Jump to: [Top](#)  Go to: [Derwent...](#) [Ema](#)Title: **JP11260372A2: MANUFACTURE OF NONAQUEOUS SECONDARY B**Country: **JP Japan**Kind: **A**Inventor: **FURUKAWA SANEHIRO;
FUJIMOTO MASAHISA;
YOSHINAGA NORIYUKI;
UENO KOJI;**Assignee: **SANYO ELECTRIC CO LTD**
[News, Profiles, Stocks and More about this company](#)Published / Filed: **1999-09-24 / 1999-01-14**Application Number: **JP1999000008215**IPC Code: **H01M 4/66; H01M 2/02; H01M 4/02; H01M 10/40;**Priority Number: **1999-01-14 JP1999019998215**


Abstract:

PROBLEM TO BE SOLVED: To improve the cycle characteristic and load characteristic, while preventing the elution of a collector by constructing a positive electrode collector and/or a positive electrode armor of aluminum with aluminum oxide coating on the surface and having lithium intercalate into a negative electrode material by injecting an electrolyte.

SOLUTION: A positive electrode collector is constructed of an aluminum foil with the surface covered with aluminum oxide. By mixing petroleum coke with N-methylpyrrolidone solution, in which polyvinylidene fluoride is dissolved, a mixed solution is prepared. Next, by applying this mix solution to a negative electrode collector made of copper foil and then bringing the negative collector into contact with lithium foil, a negative electrode 2 is formed. Lithium on the negative electrode 2 is intercalated into the petroleum coke serving as a negative electrode material after injecting the electrolyte. Then, a separator 3 is arranged between the positive electrode 1 and the negative electrode 2, and these are wound up into a spiral shape and form a group 4 of electrodes.

COPYRIGHT: (C)1999,JPO

Family: **None**Other Abstract Info: **DERABS C1999-596408 DERABS C1999-596408**



[Nominate](#)

[this for the Gallery...](#)

© 1997-2003 Thomson Delphion

[Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact](#)



(19)

(11) Publication number: **11**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **11008215**(51) Intl. Cl.: **H01M 4/66 H01M 2/02 H01M 10/40**(22) Application date: **14.01.99**

(30) Priority:	(71) Applicant: SANYO ELECTRIC CO
(43) Date of application publication: 24.09.99	(72) Inventor: FURUKAWA SANEHIRO FUJIMOTO MASAHIRO YOSHINAGA NORIYUK UENO KOJI
(84) Designated contracting states:	(74) Representative:

**(54) MANUFACTURE OF
NONAQUEOUS
SECONDARY BATTERY**


(57) Abstract:

PROBLEM TO BE SOLVED: To improve the cycle characteristic and load characteristic, while preventing the elution of a collector by constructing a positive electrode collector and/or a positive electrode armor of aluminum with aluminum oxide coating on the surface and having lithium intercalate into a negative electrode material by injecting an electrolyte.

SOLUTION: A positive electrode collector is constructed of an aluminum foil with the surface covered with aluminum oxide. By mixing petroleum coke with N-methylpyrrolidone solution, in which polyvinylidene fluoride is dissolved, a mixed solution is prepared. Next, by applying this mix solution to a

negative electrode collector made of copper foil and then bringing the negative collector into contact with lithium foil, a negative electrode 2 is formed. Lithium on the negative electrode 2 is intercalated into the petroleum coke serving as a negative electrode material after injecting the electrolyte. Then, a separator 3 is arranged between the positive electrode 1 and the negative electrode 2, and these are wound up into a spiral shape and form a group 4 of electrodes.

COPYRIGHT: (C)1999, JPO





(19)

(11) Publication number: **11**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **11008215**(51) Intl. Cl.: **H01M 4/66 H01M 2/02 H01M 10/40**(22) Application date: **14.01.99**

<p>(30) Priority:</p> <p>(43) Date of application publication: 24.09.99</p> <p>(84) Designated contracting states:</p>	<p>(71) Applicant: SANYO ELECTRIC CO</p> <p>(72) Inventor: FURUKAWA SANEHIRO FUJIMOTO MASAHIRO YOSHINAGA NORIYUK UENO KOJI</p> <p>(74) Representative:</p>
---	--

**(54) MANUFACTURE OF
NONAQUEOUS
SECONDARY BATTERY**

(57) Abstract:

PROBLEM TO BE SOLVED: To improve the cycle characteristic and load characteristic, while preventing the elution of a collector by constructing a positive electrode collector and/or a positive electrode armor of aluminum with aluminum oxide coating on the surface and having lithium intercalate into a negative electrode material by injecting an electrolyte.

SOLUTION: A positive electrode collector is constructed of an aluminum foil with the surface covered with aluminum oxide. By mixing petroleum coke with N-methylpyrrolidone solution, in which polyvinylidene fluoride is dissolved, a mixed solution is prepared. Next, by applying this mix solution to a

negative electrode collector made of copper foil and then bringing the negative collector into contact with lithium foil, a negative electrode 2 is formed. Lithium on the negative electrode 2 is intercalated into the petroleum coke serving as a negative electrode material after injecting the electrolyte. Then, a separator 3 is arranged between the positive electrode 1 and the negative electrode 2, and these are wound up into a spiral shape and form a group 4 of electrodes.

COPYRIGHT: (C)1999,JPO

